



# Accessories for CORFLEX\* II RA90 (XLPE) 600 Volts

Copper or ACM Aluminum Conductors – Connector, Hub, Knockout and Aluminum Clip Sizes

Type D





Type W



Connector Size (Type D or W)	Hub Size	Knockout Opening		Cable Support (Nexans Cat. No.)	
		mm	in	No PVC Jacket	With PVC Jacket
13	1/2	22	7/8	CS6	CS6
16	1/2	22	7/8	CS6	CS7
20	3/4	29	1 1/8	CS10	CS10
25	3/4	29	1 1/8	CS12	CS13
30	1	35	1 3/8	CS14	C14
35	1 1/4	44	1 3/4	CS15	CS16
40	1 1/4	44	1 3/4	CS17	CS18
45	1 1/2	51	2	CS19	CS19
50	2	64	2 1/2	CS20	CS21

## CS Clips Aluminum clips for round cables



Clip No.	Dimensions (mm)	
	"O"	"W"
CS7	19.4	25.4
CS10	19.4	25.4
CS12	23.0	25.4
CS13	29.3	25.4
CS14	32.5	25.4
CS15	35.7	25.4
CS16	39.3	25.4
CS17	42.4	25.4
CS18	45.6	25.4
CS19	48.8	25.4
CS20	52.3	25.4

\*\*Diameter of hole (D) = 6.65mm for all CS clips